

## EPS - XPS ADHESIVE FOAM

TECHNICAL DATA SHEET  
Version 2.0 – Revised 2024



## Product Description


**High Quality Fast Curing Adhesive Foam** for the installation of thermal insulation boards: EPS, XPS and Styrofoam. Excellent thermal & acoustic insulation.

## Approvals




## Features

- Quick and easy to apply
- Excellent adhesion to most building material
- Thermal & Acoustical Insulation
- Vibration and shock resistant
- Moisture / Mold resistant
- Ozone friendly (propellants CFC and HCFC free )
- Resistant to temperature extremes -30°C to +80°C
- Ageing Resistant



HIGH  
INSULATION



CONTROLLED  
EXPANSION



PAINTABLE



SUPERIOR  
ADHESION

## EPS - XPS ADHESIVE FOAM

TECHNICAL DATA SHEET  
Version 2.0 – Revised 2024



### Packaging



750 mL  
Can



12 units  
/ box



120 boxes  
/ pallet

### Shelf Life



15  
Months



Proper  
Storage

+ 27°C

+ 5°C

### Technical Data

Property	Unit	Value
Density	g/cm <sup>3</sup>	0.016 – 0.021
Skin Formation	Min	5 – 7
Cutting time @23°C to 30°C	Min	30 – 40
Temperature Resistance	° C	-35 to +80

### Instructions

Shake the can very well. Remove protective cap, screw onto gun. Apply the foam in beads of size 3cm leaving 2cm space at the edges of the insulation panels. Wait up to 4 mins then press the insulation panels holding them in place for 1 min. For the next 20 minutes, the panels can be corrected. Allow to cure. After curing, excess may be removed mechanically, and the cured foam should be protected against UV radiation



### Surface Preparation

Surfaces must be clean, dry and free from grease, dust and frost. In case of renovation work, old sealant as well as old paints must be removed completely. Can should be at room temperature (may be achieved by immersing in warm – NOT hot water).

### Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department. Surface should be dampened.

*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*