

ZINC GALVANIZING SPRAY

TECHNICAL DATA SHEET
Version 1.0 – Revised 2024



Product Description

Professional High Performance Spray with special zinc dust specially formulated for repairing old galvanizing surfaces & top cold coating surfaces. Actively fights rust and corrosion and provides protection of hot dip galvanize with on the job convenience.

Approvals



Features

- Quick to dry
- Easy to apply
- Weather resistant
- High coverage
- Interior/Exterior application
- CFC free
- Superior adhesion



**WEATHER
RESISTANT**



**QUICK
TO DRY**



**HIGH
COVERAGE**




**SUPERIOR
ADHESION**

ZINC GALVANIZING SPRAY

TECHNICAL DATA SHEET
Version 1.0 – Revised 2024




Packaging



Technical Data

Property	Unit	Value
Base		Solvent Based
Touch to Dry	Mins	7
Inner Pressure	MPa	0.42 ± 0.10
Spray Rate	%	≥ 95
Leak Test		Negative

Shelf Life



Instructions

Shake can vigorously for at least one minute after rattling of mixing ball is heard. While in use, shake intermittently to ensure color uniformity and to prevent clogging.

Hold the can approximately 30 cm from the object to be sprayed. Press spray button firmly while moving can back and forth. Finger must not protrude over front edge of spray button at any time.

Keep can in level line with surface and do not apply continuous spray.

For best results, apply 2 to 3 thin coats with intermittence of 10 minutes. Once applied, if product were to bubble, foam or run then you are too close to the surface or coat is too heavy.

After use, clear out the paint can's nozzle. To do so, hold the can upside down, depress the nozzle and keep spraying until only gas emerges.

Toss empty can in trash.

Do not puncture can or subject to high heat or flame.

Safety Precautions

Keep upright and away from children

Can contents under pressure. Do not puncture or burn. Shelter from direct sunlight. Do not store at temperatures exceeding 50°C.

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.